



TEST REPORT

Test item description: Automatic Pool Cover Control Box
Trademark(s): Landy
Model/Type reference: 2150-DC, 2150-AC, 4500, 9500
Applicant's name: Landy (Guangzhou) Plastic Products Co., Ltd
Address: No. 215 Shipai Industrial Zone, Dongchong Town, Nansha District, Guangzhou, China
Manufacturer: Landy (Guangzhou) Plastic Products Co., Ltd
Address: No. 215 Shipai Industrial Zone, Dongchong Town, Nansha District, Guangzhou, China
Prepared By: Shenzhen CTB Testing Technology Co., Ltd.
Address: 1&2/F., Building A, No.26, Xinxhe Road, Xinqiao, Xinqiao Street, Bao'an District, Shenzhen, Guangdong, China
Sample Received Date: Sep. 01, 2025
Sample tested Date: Sep. 01, 2025 to Oct. 14, 2025
Issue Date: Oct. 14, 2025
Report No.: CTB25090108101RH02
Test Standards: EN 62479:2010
EN 50663:2017
Test Results: PASS
Remark: This is RED health test report.

Compiled by:

Reviewed by:

Approved by:

Kai Chen

Martin Feng



Kai Chen

Martin Feng

Bin Meng, Director

Note: If there is any objection to the inspection results in this report, please submit a written report to the company within 15 days from the date of receiving the report. The test report is effective only with both signature and specialized stamp. This result(s) shown in this report refer only to the sample(s) tested. Without written approval of Shenzhen CTB Testing Technology Co., Ltd. this report can't be reproduced except in full. The tested sample(s) and the sample information are provided by the client. "*" indicates the testing items were fulfilled by subcontracted lab. "#" indicates the items are not in CNAS accreditation scope.



TABLE OF CONTENTS

1. VERSION 3

2. GENERAL INFORMATION..... 4

2.1 Product Information..... 4

3. Health Requirements..... 5

3.1 Limits 5

3.2 Exposure Evaluation 6

4. EUT Photographs 7



1. VERSION

Report No.	Issue Date	Description	Approved
CTB25090108101RH02	Oct. 14, 2025	Original	Valid

2. GENERAL INFORMATION

2.1 Product Information

Model/Type reference:	2150-DC, 2150-AC, 4500, 9500
Model Difference:	All the model are the same circuit and RF module, only the name is different. Test sample model: 2150-DC
SRD:	434.05MHz
Receiver Category:	2
Hardware Version:	V1.0
Software Version:	V1.0
Max. RF output power:	5.26dBm
Type of Modulation:	FSK
Antenna installation:	Telescopic Antenna
Ratings:	Control Box: INPUT: 110~240Vac 50/60Hz 2.68A 350w OUTPUT: 25VDC 14A Remote Control: DC 12V~23A by battery

3. Health Requirements

3.1 Limits

According to Council Recommendation: the criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation.

Reference levels for electric, magnetic and electromagnetic fields (10MHz to 300GHz)

Low-power electronic and electrical equipment is deemed to comply with the provisions of this standard if it can be demonstrated using routes B, C or D that the available antenna power and/or the average total radiated power is less than or equal to the applicable low-power exclusion level P_{max}.

Annex A contains example values for P_{max} derived from existing exposure limits listed in the bibliography, such as the ICNIRP guidelines [1], IEEE Std C95.1-1999 [2], and IEEE Std C95.1-2005 [3].

For wireless devices operated close to a person's body with available antenna powers and/or average total radiated powers higher than the P_{max} values given in Annex A, the alternative P_{max} values (called P_{max}'), described in Annex B can also be used.

For low power equipment using pulsed signals, other limits may apply in addition to those considered in Annex A and Annex B. Both ICNIRP guidelines [1] and IEEE standards [2], [3] have specific restrictions on exposures to pulsed fields, and the requirements of those standards with respect to exposure to pulses shall be met. Annex C discusses this topic further.

Exposure tier	Region of body	Exclusion level P _{max}
General public	Head and trunk	20mW(13dBm)
General public	Limbs	40mW(16dBm)

3.2 Exposure Evaluation

Mode	The worst e.i.r.p. (dBm)	Pmax(dBm)	Result
SRD	5.26	13	PASS

Remark:

1, Refer to RF test report for e.i.r.p.

2, After performed the test at low/middle/high channel, the record is the worst.

4. EUT Photographs

Refer to Report No.: CTB25090108101RE03 for EUT external and internal photos.

***** END OF REPORT *****